

Garant
GARANT Master Tap machine tap Form B 6GX, ALTiX, M: M10

Order data

Order number	132724 M10
GTIN	4045197900531
Item class	11I

Description
Version:
Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 3X 6GX

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank $\varnothing D_s$: 10 mm

Shank square \square : 8 mm

Tapping hole \varnothing : 8.5 mm

Technical description

Thread pitch	1.5 mm
Standard	DIN 371
Number of clamping slots	3
Overall length L	100 mm
Tapping hole \varnothing	8.5 mm
Thread depth	30 mm
Shank square \square	8 mm

Tolerance class	ISO 3X 6GX
Thread Ø	10 mm
Number of cutting edges Z	3
Shank Ø D _s	10 mm
Tool material	HSS E PM
Thread type	M
Thread size	M10
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap