

GARANT Master Tap machine tap Form B 6GX, AlTiX, M: M12



Order data

Order number	132724 M12
GTIN	4045197900548
Item class	111

Description

Version:

Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M

Tool material: HSS E PM Standard: DIN 376

Tolerance class: ISO 3X 6GX Thread pitch: 1.75 mm Overall length L: 110 mm

Shank Ø D_s: 9 mm Shank square □: 7 mm Tapping hole Ø: 10.2 mm

Technical description

Thread Ø	12 mm
Thread depth	36 mm
Tapping hole ∅	10.2 mm
Shank square □	7 mm
Thread pitch	1.75 mm
Number of clamping slots	3

Shank Ø D₅	9 mm
Tool material	HSS E PM
Tolerance class	ISO 3X 6GX
Standard	DIN 376
Number of cutting edges Z	3
Overall length L	110 mm
Thread type	M
Thread size	M12
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар