Garant

GARANT Master Tap machine tap Form B 6GX, AlTiX, M: M2



Order data

Order number	132724 M2
GTIN	4045197899750
Item class	111

Description

Version:

Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M Tool material: HSS E PM Standard: DIN 371 Tolerance class: ISO 3X 6GX Thread pitch: 0.4 mm Overall length L: 45 mm Shank Ø D₅: 2.8 mm Shank square □: 2.1 mm Tapping hole Ø: 1.6 mm

Technical description

Overall length L	45 mm
Shank Ø D _s	2.8 mm
Number of cutting edges Z	2
Shank square 🗆	2.1 mm
Thread pitch	0.4 mm
Number of clamping slots	2
Thread Ø	2 mm

© Hoffmann GmbH Qualitätswerkzeuge

Tapping hole \varnothing	1.6 mm
Thread depth	6 mm
Tool material	HSS E PM
Tolerance class	ISO 3X 6GX
Standard	DIN 371
Thread type	М
Thread size	M2
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар