Garant

GARANT Master Tap machine tap Form B 6GX, AlTiX, M: M20



Order data

Order number	132724 M20
GTIN	4045197900579
Item class	111

Description

Version:

Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- $\cdot\,$ Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M Tool material: HSS E PM Standard: DIN 376 Tolerance class: ISO 3X 6GX Thread pitch: 2.5 mm Overall length L: 140 mm Shank \emptyset D_s: 16 mm Shank square \Box : 12 mm Tapping hole \emptyset : 17.5 mm

Technical description

Tool material	HSS E PM
Shank square 🗆	12 mm
Thread depth	60 mm
Number of cutting edges Z	4
Tapping hole Ø	17.5 mm
Thread pitch	2.5 mm

Tolerance class	ISO 3X 6GX
Standard	DIN 376
Number of clamping slots	4
Shank Ø D _s	16 mm
Thread Ø	20 mm
Overall length L	140 mm
Thread type	М
Thread size	M20
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар