

Garant
GARANT Master Tap machine tap Form B 6GX, ALTiX, M: M24

Order data

Order number	132724 M24
GTIN	4045197900586
Item class	111

Description
Version:
Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 3X 6GX

Thread pitch: 3 mm

Overall length L: 160 mm

Shank \varnothing D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole \varnothing : 21 mm

Technical description

Shank square □	14.5 mm
Thread \varnothing	24 mm
Thread depth	72 mm
Number of cutting edges Z	4
Overall length L	160 mm
Tool material	HSS E PM

Tolerance class	ISO 3X 6GX
Standard	DIN 376
Number of clamping slots	4
Thread pitch	3 mm
Tapping hole Ø	21 mm
Shank Ø D _s	18 mm
Thread type	M
Thread size	M24
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap