

GARANT Master Tap machine tap Form B 6GX, AlTiX, M: M3



Order data

Order number	132724 M3
GTIN	4045197900487
Item class	111

Description

Version:

Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M

Tool material: HSS E PM Standard: DIN 371

Tolerance class: ISO 3X 6GX Thread pitch: 0.5 mm Overall length L: 56 mm Shank Ø D_s: 3.5 mm Shank square □: 2.7 mm Tapping hole Ø: 2.5 mm

Technical description

Thread pitch	0.5 mm
Number of clamping slots	3
Number of cutting edges Z	3
Thread depth	9 mm
Shank square □	2.7 mm
Standard	DIN 371
Tool material	HSS E PM

Tolerance class	ISO 3X 6GX
Shank Ø D _s	3.5 mm
Overall length L	56 mm
Tapping hole Ø	2.5 mm
Thread Ø	3 mm
Thread type	M
Thread size	M3
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар