

GARANT Master Tap machine tap Form B 6GX, AlTiX, M: M5



Order data

Order number	132724 M5
GTIN	4045197900500
Item class	111

Description

Version:

Tolerance class: ISO 3X/6GX

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- · HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M

Tool material: HSS E PM Standard: DIN 371

Tolerance class: ISO 3X 6GX Thread pitch: 0.8 mm Overall length L: 70 mm Shank Ø D_s: 6 mm

Shank square □: 4.9 mm Tapping hole Ø: 4.2 mm

Technical description

Thread pitch	0.8 mm
Overall length L	70 mm
Tool material	HSS E PM
Number of clamping slots	3
Tolerance class	ISO 3X 6GX
Tapping hole Ø	4.2 mm
Shank square □	4.9 mm

Number of cutting edges Z	3
Thread Ø	5 mm
Thread depth	15 mm
Standard	DIN 371
Shank Ø D _s	6 mm
Thread type	M
Thread size	M5
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	В
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар