Garant

GARANT Master Tap machine tap left-hand thread HSS-E-PM 6HX, AlTiX, M-LH: M4



Order data

| Order number | 132805 M4 |
|--------------|---------------|
| GTIN | 4045197900685 |
| Item class | 111 |

Description

Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for maximum wear resistance.
- Reduced coefficient of friction due to the new high-performance coating.
- Special geometry for optimum swarf evacuation.

Thread type: M-LH Tool material: HSS E PM Standard: DIN 371 Tolerance class: ISO 2X 6HX Thread pitch: 0.7 mm Overall length L: 63 mm Shank \emptyset D_s: 4.5 mm Shank square \Box : 3.4 mm Tapping hole \emptyset : 3.3 mm

Technical description

| Standard | DIN 371 |
|------------------------|------------|
| Thread depth | 12 mm |
| Tool material | HSS E PM |
| Shank Ø D _s | 4.5 mm |
| Tolerance class | ISO 2X 6HX |

| Thread Ø | 4 mm |
|----------------------------------|-----------------------------------|
| Thread pitch | 0.7 mm |
| Tapping hole Ø | 3.3 mm |
| Shank square 🗆 | 3.4 mm |
| Number of cutting edges Z | 3 |
| Number of clamping slots | 3 |
| Overall length L | 63 mm |
| Thread type | M-LH |
| Thread size | M4 LH |
| Coating | AlTiX |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | В |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for through holes |
| Cutting direction | left-hand |
| Type of threading tool | Machine tap for dynamic machining |
| Colour ring | green |
| Series | GARANT Master Tap |
| Type of product | Тар |