

Garant
Machine tap, TiCN, M: 12X1,5

Order data

Order number	132861 12X1,5
GTIN	4045197745736
Item class	11H

Description
Version:
Sturdy version.
Recommendation:

For **very hard steels, TOOLOX and HARDOX materials** we recommend **deviating from the DIN data** (see table) by **drilling the core hole \varnothing 0.05 to 0.3 mm** larger. For use only with a length compensation chuck – even on machines with synchronised spindle drives.

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 100 mm

 Shank \varnothing D_s: 9 mm

Shank square □: 7 mm

 Tapping hole \varnothing : 10.5 mm

Technical description

Thread pitch	1.5 mm
Number of clamping slots	5
Shank \varnothing D _s	9 mm
Number of cutting edges Z	5
Overall length L	100 mm
Thread \varnothing	12 mm

Shank square □	7 mm
Tapping hole Ø	10.5 mm
Tool material	HSS E PM
Tolerance class	ISO 2X 6HX
Standard	DIN 374
Thread depth	18 mm
Thread type	MF
Thread size	M12×1.5
Coating	TiCN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap