

Garant
Machine tap, uncoated, G: G3/8

Order data

Order number	133300 G3/8
GTIN	4045197074522
Item class	11H

Description
Version:
With spiral point.
Application:
For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Tool material: HSS E

Threads per inch: 19

 Thread \varnothing : 16.66 mm

Overall length L: 100 mm

 Shank \varnothing D_s: 12 mm

 Shank square \square : 9 mm

 Tapping hole \varnothing : 15.25 mm

Technical description

Tapping hole \varnothing	15.25 mm
Threads per inch	19
Number of cutting edges Z	3
Number of clamping slots	3
Thread \varnothing	16.66 mm
Thread pitch	1.337 mm
Tool material	HSS E
Shank \varnothing D _s	12 mm

Overall length L	100 mm
Shank square □	9 mm
Thread depth	49.98 mm
Thread size	G3/8
Coating	uncoated
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap