

Garant
Machine tap, TiCN, G: G3/4

Order data

Order number	133310 G3/4
GTIN	4045197446213
Item class	11H

Description
Version:
With spiral point.

For use with **emulsion** (fat content minimum 8 %).

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Recommendation:

For **TOOLOX materials** we recommend **deviating from the DIN data** (see table) by drilling the tapping hole \varnothing **0.05 to 0.3 mm** larger.

Tool material: HSS

Threads per inch: 14

Thread \varnothing : 26.44 mm

Overall length L: 140 mm

Shank \varnothing D_s: 20 mm

Shank square □: 16 mm

Tapping hole \varnothing : 24.5 mm

Technical description

Number of cutting edges Z	4
Number of clamping slots	4
Threads per inch	14
Tapping hole \varnothing	24.5 mm
Thread \varnothing	26.44 mm

Thread pitch	1.814 mm
Tool material	HSS
Shank $\varnothing D_s$	20 mm
Overall length L	140 mm
Shank square \square	16 mm
Thread depth	79.32 mm
Thread size	G3/4
Coating	TiCN
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap