

Garant
Machine tap, TiCN, G: G3/8 inch

Order data

Order number	133315 G3/8
GTIN	4045197746092
Item class	11H

Description
Version:
Sturdy version.
Recommendation:

For very hard steels, TOOLOX and HARDOX materials we recommend **deviating from the DIN data (see table) by drilling the tapping \varnothing 0.05 to 0.3 mm larger.**

For use only with a length compensation chuck – even on machines with synchronised spindle drives.

Tool material: HSS E PM

Threads per inch: 19

Thread \varnothing : 16.66 mm

Overall length L: 100 mm

Shank \varnothing D_s: 12 mm

Shank square \square : 9 mm

Tapping hole \varnothing : 15.25 mm

Technical description

Thread pitch	1.337 mm
Shank \varnothing D _s	12 mm
Number of cutting edges Z	5
Number of clamping slots	5
Thread \varnothing	16.66 mm
Shank square \square	9 mm
Tapping hole \varnothing	15.25 mm

Threads per inch	19
Tool material	HSS E PM
Overall length L	100 mm
Thread depth	24 mm
Thread size	G3/8
Coating	TiCN
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5xD for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap