

Garant
GARANT Master Tap machine tap HSS-E-PM, ALTiX, G: G3/4 inch

Order data

Order number	133330 G3/4
GTIN	4045197901194
Item class	111

Description
Version:

GARANT Master Tap Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Tool material: HSS E PM

Threads per inch: 14

Thread Ø: 26.44 mm

Overall length L: 140 mm

Shank Ø D_s: 20 mm

Shank square □: 16 mm

Tapping hole Ø: 24.5 mm

Technical description

Tapping hole Ø	24.5 mm
Overall length L	140 mm
Number of cutting edges Z	2
Shank square □	16 mm
Number of clamping slots	2

Tool material	HSS E PM
Thread depth	79.32 mm
Shank $\varnothing D_s$	20 mm
Thread \varnothing	26.44 mm
Thread pitch	1.814 mm
Threads per inch	14
Thread size	G3/4
Series	GARANT Master Tap
Coating	AlTiX
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap