

**Garant**
**GARANT Master Tap machine tap HSS-E-PM, ALTiX, G: G5/8 inch**

**Order data**

Order number	133330 G5/8
GTIN	4045197901187
Item class	111

**Description**
**Version:**

**GARANT Master Tap Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

**Application:**

**For Whitworth parallel pipe threads** DIN-ISO 228/1 (threads that do not form a seal within the connection).

Tool material: HSS E PM

Threads per inch: 14

Thread Ø: 22.91 mm

Overall length L: 125 mm

Shank Ø D<sub>s</sub>: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 21 mm

**Technical description**

Thread Ø	22.91 mm
Threads per inch	14
Thread depth	68.73 mm
Number of clamping slots	4
Overall length L	125 mm

Thread pitch	1.814 mm
Tapping hole Ø	21 mm
Shank square □	14.5 mm
Shank Ø D <sub>s</sub>	18 mm
Tool material	HSS E PM
Number of cutting edges Z	4
Thread size	G5/8
Series	GARANT Master Tap
Coating	AlTiX
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap