

Machine tap, uncoated, UNC: 1/2-13



Order data

| Order number | 133350 1/2-13 |
|--------------|---------------|
| GTIN | 4045197074690 |
| Item class | 11H |

Description

Version:

With spiral point.

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC
Tool material: HSS E
Standard: DIN 376
Threads per inch: 13
Thread Ø: 12.7 mm

Overall length L: 110 mm

Shank Ø D₅: 9 mm Shank square □: 7 mm Tapping hole Ø: 10.8 mm

Technical description

| Number of cutting edges Z | 3 |
|---------------------------|---------|
| Thread pitch | 1.95 mm |
| Threads per inch | 13 |
| Tapping hole ∅ | 10.8 mm |
| Number of clamping slots | 3 |
| Thread Ø | 12.7 mm |
| Tool material | HSS E |

| Standard | DIN 376 |
|----------------------------------|--|
| Shank Ø D _s | 9 mm |
| Overall length L | 110 mm |
| Shank square □ | 7 mm |
| Thread depth | 38.1 mm |
| Thread type | UNC |
| Thread size | 1/2-13 UNC |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Tolerance class | 2B |
| Taper lead form | В |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for through holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for conventional machining |
| Colour ring | without |
| Type of product | Тар |