

Garant
Machine tap, uncoated, UNC: 3/8-16

Order data

Order number	133350 3/8-16
GTIN	4045197074676
Item class	11H

Description
Version:
With spiral point.
Application:
For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E

Standard: DIN 371

Threads per inch: 16

 Thread \varnothing : 9.53 mm

Overall length L: 100 mm

 Shank \varnothing D_s: 9 mm

 Shank square \square : 7 mm

 Tapping hole \varnothing : 8 mm

Technical description

Tapping hole \varnothing	8 mm
Threads per inch	16
Thread pitch	1.587 mm
Number of cutting edges Z	3
Thread \varnothing	9.53 mm
Number of clamping slots	3
Standard	DIN 371
Tool material	HSS E

Shank $\varnothing D_s$	9 mm
Overall length L	100 mm
Shank square \square	7 mm
Thread depth	28.56 mm
Thread type	UNC
Thread size	3/8-16 UNC
Coating	uncoated
Flank angle	60 degrees
Tolerance class	2B
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap