

Garant
Machine tap, uncoated, UNC: 5-40

Order data

Order number	133350 5-40
GTIN	4045197074607
Item class	11H

Description
Version:
With spiral point.
Application:
For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E

Standard: DIN 371

Threads per inch: 40

 Thread \varnothing : 3.17 mm

Overall length L: 56 mm

 Shank \varnothing D_s: 3.5 mm

 Shank square \square : 2.7 mm

 Tapping hole \varnothing : 2.65 mm

Technical description

Thread \varnothing	3.17 mm
Thread pitch	0.635 mm
Number of clamping slots	3
Number of cutting edges Z	3
Threads per inch	40
Tapping hole \varnothing	2.65 mm
Standard	DIN 371
Tool material	HSS E

Shank $\varnothing D_s$	3.5 mm
Overall length L	56 mm
Shank square \square	2.7 mm
Thread depth	9.51 mm
Thread type	UNC
Thread size	5-40 UNC
Coating	uncoated
Flank angle	60 degrees
Tolerance class	2B
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap