

Garant
Machine tap, uncoated, UNC: 7/8-9

Order data

Order number	133350 7/8-9
GTIN	4045197074720
Item class	11H

Description
Version:
With spiral point.
Application:
For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E

Standard: DIN 376

Threads per inch: 9

Thread Ø: 22.23 mm

Overall length L: 140 mm

 Shank Ø D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 19.5 mm

Technical description

Number of clamping slots	3
Thread Ø	22.23 mm
Number of cutting edges Z	3
Threads per inch	9
Tapping hole Ø	19.5 mm
Thread pitch	2.822 mm
Standard	DIN 376

Tool material	HSS E
Shank $\varnothing D_s$	18 mm
Overall length L	140 mm
Shank square \square	14.5 mm
Thread depth	66.66 mm
Thread type	UNC
Thread size	7/8-9 UNC
Coating	uncoated
Flank angle	60 degrees
Tolerance class	2B
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap