

Garant
Machine taps, uncoated, M: M3,5

Order data

Order number	134600 M3,5
GTIN	4045197075406
Item class	11H

Description
Version:
Sturdy design, with 15 – 20° right-hand helix.

Size M2.6 has the old DIN profile.

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 0.6 mm

Overall length L: 56 mm

 Shank $\varnothing D_s$: 4 mm

 Shank square \square : 3 mm

 Tapping hole \varnothing : 2.9 mm

Technical description

Tapping hole \varnothing	2.9 mm
Number of clamping slots	3
Thread \varnothing	3.5 mm
Number of cutting edges Z	3
Thread pitch	0.6 mm
Standard	DIN 371
Shank $\varnothing D_s$	4 mm
Overall length L	56 mm

Shank square <input type="checkbox"/>	3 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	7 mm
Thread type	M
Thread size	M3.5
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	D
Helix angle	15-20 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap