

**Garant**
**Machine taps, uncoated, M: M9**

**Order data**

Order number	134600 M9
GTIN	4045197075475
Item class	11H

**Description**
**Version:**
**Sturdy design, with 15 – 20° right-hand helix.**

Size M2.6 has the old DIN profile.

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 1.25 mm

Overall length L: 90 mm

 Shank  $\varnothing D_s$ : 9 mm

 Shank square  $\square$ : 7 mm

 Tapping hole  $\varnothing$ : 7.8 mm

**Technical description**

Number of clamping slots	3
Thread pitch	1.25 mm
Number of cutting edges Z	3
Thread $\varnothing$	9 mm
Tapping hole $\varnothing$	7.8 mm
Standard	DIN 371
Shank $\varnothing D_s$	9 mm
Overall length L	90 mm

Shank square <input type="checkbox"/>	7 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	18 mm
Thread type	M
Thread size	M9
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	D
Helix angle	15-20 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap