

Garant
Machine tap, TiCN, M: M10

Order data

Order number	135320 M10
GTIN	4045197076502
Item class	11H

Description
Version:

With strong right-hand chip flutes, for optimum swarf evacuation.

For use with **emulsion** (fat content minimum 8%).

Recommendation:

For **TOOLOX materials we recommend deviating from the DIN data** (see table) by drilling the tapping hole \varnothing **0.05** to **0.3 mm** larger.

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 1.5 mm

Overall length L: 100 mm

Shank \varnothing D_s: 10 mm

Shank square □: 8 mm

Tapping hole \varnothing : 8.5 mm

Technical description

Number of cutting edges Z	3
Tapping hole \varnothing	8.5 mm
Thread \varnothing	10 mm
Number of clamping slots	3
Thread pitch	1.5 mm
Standard	DIN 371
Shank \varnothing D _s	10 mm

Overall length L	100 mm
Shank square □	8 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	20 mm
Thread type	M
Thread size	M10
Coating	TiCN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2xD for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap