

Garant
Machine tap HSS-E-PM, TiN / vaporised, M: M30

Order data

Order number	135375 M30
GTIN	4045197747235
Item class	11H

Description
Version:

For use with **emulsion** (fat content minimum 8%).

For use with **emulsion** (fat content minimum 8%).

Recommendation:

For **TOOLOX** and **HARDOX materials** we recommend **deviating from the DIN data** (see table) by drilling the tapping hole \varnothing **0.05** to **0.3 mm** larger.

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 3.5 mm

Overall length L: 180 mm

Shank \varnothing D_s: 22 mm

Shank square □: 18 mm

Tapping hole \varnothing : 26.5 mm

Technical description

Shank square □	18 mm
Overall length L	180 mm
Standard	DIN 376
Tapping hole \varnothing	26.5 mm
Thread \varnothing	30 mm
Number of cutting edges Z	4

Shank $\varnothing D_s$	22 mm
Thread pitch	3.5 mm
Tolerance class	ISO 2 6H
Number of clamping slots	4
Tool material	HSS E PM
Thread depth	90 mm
Thread type	M
Thread size	M30
Coating	TiN / vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap