

**Garant**
**Machine tap HSS-E-PM, TiN, M: M16**

**Order data**

Order number	135378 M16
GTIN	4045197649508
Item class	11H

**Description**
**Version:**

For use with **emulsion** (fat content minimum 8%).

For use with **emulsion** (fat content minimum 8%).

**Recommendation:**

For **TOOLOX** and **HARDOX materials** we recommend **deviating from the DIN** data (see table) by drilling the tapping hole  $\varnothing$  **0.05** to **0.3 mm** larger.

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 2 mm

Overall length L: 110 mm

Shank  $\varnothing$  D<sub>s</sub>: 12 mm

Shank square □: 9 mm

Tapping hole  $\varnothing$ : 14 mm

**Technical description**

Number of clamping slots	3
Number of cutting edges Z	3
Thread $\varnothing$	16 mm
Thread pitch	2 mm
Tapping hole $\varnothing$	14 mm
Standard	DIN 376

Shank $\varnothing D_s$	12 mm
Overall length L	110 mm
Shank square $\square$	9 mm
Tolerance class	ISO 2 6H
Tool material	HSS E PM
Thread depth	48 mm
Thread type	M
Thread size	M16
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	25 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap