

Garant
Machine tap 6G, vaporised, M: M3

Order data

Order number	135600 M3
GTIN	4045197077066
Item class	11H

Description
Version:
Tolerance class ISO 3 / 6G = with oversize approx. 0.02 – 0.04 mm. **HSS-E**
Application:

 For components which are **galvanised** after threading or shrink slightly when hardened.

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 3 6G

Thread pitch: 0.5 mm

Overall length L: 56 mm

 Shank $\varnothing D_s$: 3.5 mm

 Shank square \square : 2.7 mm

 Tapping hole \varnothing : 2.5 mm

Technical description

Number of clamping slots	3
Tapping hole \varnothing	2.5 mm
Thread \varnothing	3 mm
Thread pitch	0.5 mm
Number of cutting edges Z	3
Standard	DIN 371
Shank $\varnothing D_s$	3.5 mm
Overall length L	56 mm

Shank square <input type="checkbox"/>	2.7 mm
Tolerance class	ISO 3 6G
Tool material	HSS E
Thread depth	6 mm
Thread type	M
Thread size	M3
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	blue
Type of product	Tap