

**Garant**
**Machine tap HSS-E-PM, nitrided, M: M6**

**Order data**

Order number	135750 M6
GTIN	4045197077448
Item class	11H

**Description**
**Version:**
**Sturdy design, with 15° right-hand chip flutes.**

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 1 mm

Overall length L: 80 mm

 Shank  $\varnothing$  D<sub>s</sub>: 6 mm

 Shank square  $\square$ : 4.9 mm

 Tapping hole  $\varnothing$ : 5 mm

**Technical description**

Thread pitch	1 mm
Number of cutting edges Z	3
Number of clamping slots	3
Thread $\varnothing$	6 mm
Tapping hole $\varnothing$	5 mm
Standard	DIN 371
Shank $\varnothing$ D <sub>s</sub>	6 mm
Overall length L	80 mm
Shank square $\square$	4.9 mm

Tolerance class	ISO 2X 6HX
Tool material	HSS E PM
Thread depth	12 mm
Thread type	M
Thread size	M6
Coating	nitrided
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	15 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	pink
Type of product	Tap