

Garant
Machine taps HSS-E Form C, vaporised, M: M14

Order data

Order number	135850 M14
GTIN	4045197077776
Item class	11H

Description
Version:
Form C (2–3 turns lead chamfer).

Thread type: M

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 2 mm

Overall length L: 110 mm

Shank $\varnothing D_s$: 11 mmShank square \square : 9 mmTapping hole \varnothing : 12 mm
Technical description

Thread pitch	2 mm
Number of clamping slots	3
Thread \varnothing	14 mm
Tapping hole \varnothing	12 mm
Number of cutting edges Z	3
Standard	DIN 376
Shank $\varnothing D_s$	11 mm
Overall length L	110 mm
Shank square \square	9 mm

Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	42 mm
Thread type	M
Thread size	M14
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap