

Garant
Machine taps HSS-E Form C, vaporised, M: M2,3

Order data

Order number	135850 M2,3
GTIN	4045197077660
Item class	11H

Description
Version:
Form C (2–3 turns lead chamfer). With the old DIN profile.

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 0.4 mm

Overall length L: 45 mm

Shank $\varnothing D_s$: 2.8 mmShank square \square : 2.1 mmTapping hole \varnothing : 1.9 mm
Technical description

Number of clamping slots	3
Thread pitch	0.4 mm
Number of cutting edges Z	3
Tapping hole \varnothing	1.9 mm
Thread \varnothing	2.3 mm
Standard	DIN 371
Shank $\varnothing D_s$	2.8 mm
Overall length L	45 mm
Shank square \square	2.1 mm

Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	6.9 mm
Thread type	M
Thread size	M2,3
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap