



Machine taps HSS-E Form C, vaporised, M: M5



Order data

| | |
|--------------|---------------|
| Order number | 135855 M5 |
| GTIN | 4045197649546 |
| Item class | 12H |

Description

Version:

Form C (2–3 turns lead chamfer).

Thread type: M

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 2 6H

Thread pitch: 0.8 mm

Overall length L: 70 mm

Shank $\varnothing D_s$: 6 mm

Shank square \square : 4.9 mm

Tapping hole \varnothing : 4.2 mm

Technical description

| | |
|----------------------------|---------|
| Thread \varnothing | 5 mm |
| Number of clamping slots | 2 |
| Tapping hole \varnothing | 4.2 mm |
| Number of cutting edges Z | 2 |
| Thread pitch | 0.8 mm |
| Standard | DIN 371 |
| Shank $\varnothing D_s$ | 6 mm |
| Overall length L | 70 mm |
| Shank square \square | 4.9 mm |

| | |
|----------------------------------|-----------------------------------|
| Tolerance class | ISO 2 6H |
| Tool material | HSS E |
| Thread depth | 15 mm |
| Thread type | M |
| Thread size | M5 |
| Coating | vaporised |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | C |
| Helix angle | 40 degrees |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for blind holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for dynamic machining |
| Colour ring | green |
| Type of product | Tap |

Accessories

| | |
|---|--------------|
| Blind hole machine taps + tapping drills for metric threads M3-12 | 146925 M3-12 |
| Blind hole machine taps for metric threads M3-12 | 146745 M3-12 |