

**Garant**
**GARANT Master Tap machine tap HSS-E-PM Form C, ALTiX, M: M2**

**Order data**

Order number	135960 M2
GTIN	4045197899705
Item class	11I

**Description**
**Version:**

**Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Corresponds to **ISO 2X/6HX**.

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.4 mm

Overall length L: 45 mm

Shank  $\varnothing D_s$ : 2.8 mm

Shank square  $\square$ : 2.1 mm

Tapping hole  $\varnothing$ : 1.6 mm

**Technical description**

Tapping hole $\varnothing$	1.6 mm
Shank square $\square$	2.1 mm
Thread pitch	0.4 mm
Tool material	HSS E PM
Tolerance class	ISO 2X 6HX
Thread depth	5 mm
Number of cutting edges Z	3

Overall length L	45 mm
Thread Ø	2 mm
Shank Ø D <sub>s</sub>	2.8 mm
Number of clamping slots	3
Standard	DIN 371
Thread type	M
Thread size	M2
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap