

Garant
GARANT Master Tap machine tap HSS-E-PM IC / Form C 6HX, AlTiX, M: M16

Order data

Order number	135965 M16
GTIN	4045197899651
Item class	111

Description
Version:
With internal coolant feed.

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: M

Tool material: HSS E PM

Standard: DIN 376

Tolerance class: ISO 2X 6HX

Thread pitch: 2 mm

Overall length L: 110 mm

Shank \varnothing D_s: 12 mm

Shank square □: 9 mm

Tapping hole \varnothing : 14 mm

Technical description

Overall length L	110 mm
Thread pitch	2 mm
Standard	DIN 376
Number of cutting edges Z	3
Tapping hole \varnothing	14 mm
Shank square □	9 mm

Thread Ø	16 mm
Tool material	HSS E PM
Shank Ø D _s	12 mm
Tolerance class	ISO 2X 6HX
Thread depth	40 mm
Number of clamping slots	3
Thread type	M
Thread size	M16
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	yes
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap