Garant

GARANT Master Tap machine tap HSS-E-PM Form E 6HX, AlTiX, M: M20

Order data

Order number	136152 M20
GTIN	4045197900296
Item class	111

Description

Version:

Form E (1.5-2 turns lead chamfer)

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for a high degree of wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: M Tool material: HSS E PM Standard: DIN 376 Tolerance class: ISO 2X 6HX Thread pitch: 2.5 mm Overall length L: 140 mm Shank \emptyset D_s: 16 mm Shank square \Box : 12 mm Tapping hole \emptyset : 17.5 mm

Technical description

Tolerance class	ISO 2X 6HX
Shank Ø D _s	16 mm
Number of cutting edges Z	4
Thread pitch	2.5 mm
Tool material	HSS E PM
Standard	DIN 376

© Hoffmann GmbH Qualitätswerkzeuge

Data sheet

Overall length L	140 mm
Number of clamping slots	4
Thread depth	50 mm
Thread Ø	20 mm
Tapping hole Ø	17.5 mm
Shank square 🗆	12 mm
Thread type	М
Thread size	M20
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	E
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар