Garant

GARANT Master Tap machine tap HSS-E-PM Form E 6HX, AITiX, M: M4



Order data

Order number	136152 M4
GTIN	4045197900210
Item class	111

Description

Version:

Form E (1.5-2 turns lead chamfer)

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for a high degree of wear resistance.
- $\cdot\,$ Reduced coefficient of friction due to the new high-performance coating.
- $\cdot\,$ Special geometry for optimum swarf evacuation.

Thread type: M Tool material: HSS E PM Standard: DIN 371 Tolerance class: ISO 2X 6HX Thread pitch: 0.7 mm Overall length L: 63 mm Shank \emptyset D_s: 4.5 mm Shank square \Box : 3.4 mm Tapping hole \emptyset : 3.3 mm

Technical description

Tolerance class	ISO 2X 6HX
Number of clamping slots	3
Shank square 🗆	3.4 mm
Thread Ø	4 mm
Tapping hole Ø	3.3 mm
Number of cutting edges Z	3

© Hoffmann GmbH Qualitätswerkzeuge

Overall length L	63 mm
Standard	DIN 371
Thread pitch	0.7 mm
Tool material	HSS E PM
Shank Ø D _s	4.5 mm
Thread depth	10 mm
Thread type	Μ
Thread size	M4
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	E
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар