

Garant
GARANT Master Tap machine tap HSS-E-PM Form E 6HX, AlTiX, M: M5

Order data

Order number	136152 M5
GTIN	4045197900227
Item class	111

Description
Version:
Form E (1.5-2 turns lead chamfer)

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 2X 6HX

Thread pitch: 0.8 mm

Overall length L: 70 mm

Shank $\varnothing D_s$: 6 mmShank square \square : 4.9 mmTapping hole \varnothing : 4.2 mm
Technical description

Overall length L	70 mm
Shank square \square	4.9 mm
Thread depth	12.5 mm
Tool material	HSS E PM
Number of clamping slots	3
Standard	DIN 371

Tolerance class	ISO 2X 6HX
Thread pitch	0.8 mm
Number of cutting edges Z	3
Shank $\varnothing D_s$	6 mm
Tapping hole \varnothing	4.2 mm
Thread \varnothing	5 mm
Thread type	M
Thread size	M5
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	E
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5xD for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap