

Garant
GARANT Master Tap machine tap HSS-E-PM Form C 6GX, AlTiX, M: M4

Order data

Order number	136158 M4
GTIN	4045197900104
Item class	11I

Description
Version:
Tolerance class: ISO 3X/6GX

For components which are galvanised or shrink slightly when hardened.

Universal taps, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for a high degree of wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: M

Tool material: HSS E PM

Standard: DIN 371

Tolerance class: ISO 3X 6GX

Thread pitch: 0.7 mm

Overall length L: 63 mm

Shank $\varnothing D_s$: 4.5 mm

Shank square \square : 3.4 mm

Tapping hole \varnothing : 3.3 mm

Technical description

Number of cutting edges Z	3
Number of clamping slots	3
Shank $\varnothing D_s$	4.5 mm
Tolerance class	ISO 3X 6GX
Thread depth	10 mm
Thread \varnothing	4 mm

Tapping hole Ø	3.3 mm
Standard	DIN 371
Tool material	HSS E PM
Shank square □	3.4 mm
Thread pitch	0.7 mm
Overall length L	63 mm
Thread type	M
Thread size	M4
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap