

**Garant**
**Machine tap, left-hand thread HSS-E 6H, vaporised, M-LH: M12**

**Order data**

Order number	136180 M12
GTIN	4045197078445
Item class	11H

**Description**
**Version:**

**Left-hand cutting.** With **strong left-hand chip flutes**, for optimum swarf evacuation.

Thread type: M-LH

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 1.75 mm

Overall length L: 110 mm

Shank  $\varnothing D_s$ : 9 mm

Shank square  $\square$ : 7 mm

Tapping hole  $\varnothing$ : 10.2 mm

**Technical description**

Number of cutting edges Z	3
Tapping hole $\varnothing$	10.2 mm
Number of clamping slots	3
Thread pitch	1.75 mm
Thread $\varnothing$	12 mm
Standard	DIN 376
Shank $\varnothing D_s$	9 mm
Overall length L	110 mm
Shank square $\square$	7 mm

Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	36 mm
Thread type	M-LH
Thread size	M12 LH
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	left-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap