

Garant
Machine tap, left-hand thread HSS-E 6H, vaporised, M-LH: M14

Order data

Order number	136180 M14
GTIN	4045197078452
Item class	11H

Description
Version:

Left-hand cutting. With **strong left-hand chip flutes**, for optimum swarf evacuation.

Thread type: M-LH

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 2 6H

Thread pitch: 2 mm

Overall length L: 110 mm

Shank $\varnothing D_s$: 11 mm

Shank square \square : 9 mm

Tapping hole \varnothing : 12 mm

Technical description

Number of clamping slots	3
Tapping hole \varnothing	12 mm
Number of cutting edges Z	3
Thread \varnothing	14 mm
Thread pitch	2 mm
Standard	DIN 376
Shank $\varnothing D_s$	11 mm
Overall length L	110 mm
Shank square \square	9 mm

Tolerance class	ISO 2 6H
Tool material	HSS E
Thread depth	42 mm
Thread type	M-LH
Thread size	M14 LH
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	left-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Type of product	Tap