

Garant
Machine taps, vaporised, MF: 8X1

Order data

Order number	136210 8X1
GTIN	4045197078568
Item class	11H

Description
Version:

Surface vaporised for reduced edge build-up.

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 1 mm

Overall length L: 90 mm

Shank $\varnothing D_s$: 6 mm

Shank square \square : 4.9 mm

Tapping hole \varnothing : 7 mm

Technical description

Thread pitch	1 mm
Number of cutting edges Z	3
Tapping hole \varnothing	7 mm
Thread \varnothing	8 mm
Number of clamping slots	3
Shank $\varnothing D_s$	6 mm
Overall length L	90 mm
Shank square \square	4.9 mm
Tolerance class	ISO 2 6H

Tool material	HSS E
Standard	DIN 374
Thread depth	16 mm
Thread type	MF
Thread size	M8×1
Coating	vaporised
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	yellow
Type of product	Tap