

Garant
Machine taps, uncoated, M: 30X2

Order data

Order number	136250 30X2
GTIN	4045197079053
Item class	11H

Description
Version:
Sturdy design, with 15° right-hand chip flutes.

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 2 mm

Overall length L: 150 mm

 Shank $\varnothing D_s$: 22 mm

 Shank square \square : 18 mm

 Tapping hole \varnothing : 28 mm

Technical description

Tapping hole \varnothing	28 mm
Thread \varnothing	30 mm
Thread pitch	2 mm
Number of cutting edges Z	4
Number of clamping slots	4
Shank $\varnothing D_s$	22 mm
Overall length L	150 mm
Shank square \square	18 mm
Tolerance class	ISO 2 6H

Tool material	HSS E
Standard	DIN 374
Thread depth	60 mm
Thread type	MF
Thread size	M30×2
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	15 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap