

**Garant**
**Machine tap HSS-E, TiCN, M: 24X1,5**

**Order data**

Order number	136270 24X1,5
GTIN	4045197079435
Item class	11H

**Description**
**Version:**

For use with **emulsion** (fat content minimum 8%).

**Recommendation:**

For **TOOLOX materials we recommend deviating from the DIN data** (see table) by drilling the tapping hole  $\varnothing$  **0.05** to **0.3 mm** larger.

Thread type: MF

Tool material: HSS E

Standard: DIN 374

Tolerance class: ISO 2 6H

Thread pitch: 1.5 mm

Overall length L: 140 mm

Shank  $\varnothing$  D<sub>s</sub>: 18 mm

Shank square □: 14.5 mm

Tapping hole  $\varnothing$ : 22.5 mm

**Technical description**

Tapping hole $\varnothing$	22.5 mm
Number of cutting edges Z	5
Thread $\varnothing$	24 mm
Number of clamping slots	5
Thread pitch	1.5 mm
Shank $\varnothing$ D <sub>s</sub>	18 mm
Overall length L	140 mm

Shank square □	14.5 mm
Tolerance class	ISO 2 6H
Tool material	HSS E
Standard	DIN 374
Thread depth	48 mm
Thread type	MF
Thread size	M24×1.5
Coating	TiCN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	red
Type of product	Tap