## Garant

### GARANT Master Tap machine tap HSS-E-PM, AlTiX, MF: 18X1,5



### Order data

Order number	137160 18X1,5
GTIN	4045197900876
Item class	111

### Description

#### Version:

**GARANT Master Tap Universal taps,** designed for use in a wide spectrum of materials with high process reliability.

- HSS-E-PM tool material for maximum wear resistance.
- · Reduced coefficient of friction due to the new high-performance coating.
- · Special geometry for optimum swarf evacuation.

Thread type: MF Tool material: HSS E PM Standard: DIN 374 Tolerance class: ISO 2X 6HX Thread pitch: 1.5 mm Overall length L: 110 mm Shank  $\emptyset$  D<sub>s</sub>: 14 mm Shank square  $\Box$ : 11 mm Tapping hole  $\emptyset$ : 16.5 mm

#### **Technical description**

Thread Ø	18 mm
Thread depth	45 mm
Shank Ø D <sub>s</sub>	14 mm
Tapping hole Ø	16.5 mm
Shank square 🗆	11 mm
Standard	DIN 374

© Hoffmann GmbH Qualitätswerkzeuge

# Data sheet

Tool material	HSS E PM
Tolerance class	ISO 2X 6HX
Number of cutting edges Z	4
Overall length L	110 mm
Thread pitch	1.5 mm
Number of clamping slots	4
Thread type	MF
Thread size	M18×1.5
Coating	Altix
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Тар