

**Garant**
**GARANT Master Tap machine tap HSS-E-PM, ALTiX, MF: 24X1,5**

**Order data**

Order number	137160 24X1,5
GTIN	4045197900906
Item class	111

**Description**
**Version:**

**GARANT Master Tap Universal taps**, designed for use in a wide spectrum of materials with high process reliability.

- **HSS-E-PM tool material for maximum wear resistance.**
- **Reduced coefficient of friction due to the new high-performance coating.**
- **Special geometry for optimum swarf evacuation.**

Thread type: MF

Tool material: HSS E PM

Standard: DIN 374

Tolerance class: ISO 2X 6HX

Thread pitch: 1.5 mm

Overall length L: 140 mm

Shank  $\varnothing D_s$ : 18 mm

Shank square  $\square$ : 14.5 mm

Tapping hole  $\varnothing$ : 22.5 mm

**Technical description**

Shank $\varnothing D_s$	18 mm
Number of cutting edges Z	4
Number of clamping slots	4
Thread depth	60 mm
Tool material	HSS E PM
Shank square $\square$	14.5 mm

Tapping hole Ø	22.5 mm
Overall length L	140 mm
Tolerance class	ISO 2X 6HX
Thread Ø	24 mm
Standard	DIN 374
Thread pitch	1.5 mm
Thread type	MF
Thread size	M24×1.5
Coating	AlTiX
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for dynamic machining
Colour ring	green
Series	GARANT Master Tap
Type of product	Tap