

**Garant**
**Machine tap, vaporised, G: G1/2**

**Order data**

Order number	137350 G1/2
GTIN	4045197079879
Item class	11H

**Description**
**Version:**

Surface vaporised for reduced edge build-up. **HSS-E**

**Application:**

**For Whitworth parallel pipe threads** DIN-ISO 228/1 (threads that do not form a seal within the connection).

Tool material: HSS E

Threads per inch: 14

Thread Ø: 20.96 mm

Overall length L: 125 mm

Shank Ø D<sub>s</sub>: 16 mm

Shank square □: 12 mm

Tapping hole Ø: 19 mm

**Technical description**

Threads per inch	14
Thread Ø	20.96 mm
Tapping hole Ø	19 mm
Number of clamping slots	4
Number of cutting edges Z	4
Thread pitch	1.814 mm
Tool material	HSS E
Shank Ø D <sub>s</sub>	16 mm

Overall length L	125 mm
Shank square □	12 mm
Thread depth	41.92 mm
Thread size	G1/2
Coating	vaporised
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap