

Garant
Machine tap ISO 228 +0.05 mm, vaporised, G: G1/2 inch

Order data

Order number	137360 G1/2
GTIN	4045197705679
Item class	11H

Description
Version:

Surface vaporised for reduced edge build-up.

Tolerance class ISO 228 + 0.05 mm. HSS-E

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

For components which are **galvanised** after threading or shrink slightly when hardened.

Recommendation:

We recommend **deviating from the DIN data** (see table) by drilling the tapping hole \varnothing **0.05 mm larger**.

Tool material: HSS E

Threads per inch: 14

Thread \varnothing : 20.96 mm

Overall length L: 125 mm

Shank \varnothing D_s: 16 mm

Shank square □: 12 mm

Tapping hole \varnothing : 19 mm

Technical description

Thread \varnothing	20.96 mm
Thread pitch	1.814 mm
Threads per inch	14
Number of cutting edges Z	4
Number of clamping slots	4

Tapping hole Ø	19 mm
Tool material	HSS E
Shank Ø D _s	16 mm
Overall length L	125 mm
Shank square □	12 mm
Thread depth	62.88 mm
Thread size	G1/2
Coating	vaporised
Thread type	G
Flank angle	55 degrees
Standard	DIN 5156
Taper lead form	C
Helix angle	40 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap