

Garant

Machine tap for synchronised spindles HSS-E-PM Form E, TiAlN, G: G3/8 inch



Order data

Order number	137813 G3/8
GTIN	4045197705761
Item class	11H

Description

Version:

Sturdy version with right-hand helix and shank to DIN 1835-B. Special geometry for **general-purpose use** on machines with **synchronised spindle drive**. The tap is controlled by the synchronising spindle of the machine. Special **TiAlN-S coating** for optimum tool life. For use with **emulsion** (fat content minimum 8%).

Form E (lead chamfer: 1.5 - 2 turns) for the deepest possible thread depths.

Application:

For Whitworth parallel pipe threads DIN-ISO 228/1 (threads that do not form a seal within the connection).

Note:

For use on synchronised spindles, the **GARANT** quick-change tapping chuck **No. 338100 – 338121 with minimum length adjustment (MLA)** ensures very high process reliability.

Tool material: HSS E PM

Threads per inch: 19

Thread Ø: 16.66 mm

Overall length L: 100 mm

Shank Ø D_s: 12 mm

Shank square □: 9 mm

Tapping hole Ø: 15.25 mm

Technical description

Tapping hole Ø	15.25 mm
Number of clamping slots	4
Thread Ø	16.66 mm
Threads per inch	19

Thread pitch	1.337 mm
Number of cutting edges Z	4
Tool material	HSS E PM
Shank $\varnothing D_s$	12 mm
Overall length L	100 mm
Shank square \square	9 mm
Thread depth	49.98 mm
Thread size	G3/8
Coating	TiAlN
Thread type	G
Flank angle	55 degrees
Standard	Manufacturer's standard
Taper lead form	E
Helix angle	40 degrees
Shank	DIN 1835 B to h6
Through-coolant	no
Application for type of drilling	up to 3xD for blind holes
Cutting direction	right-hand
Shank tolerance	h6
Type of threading tool	Machine tap for synchronous machining
Colour ring	green
Type of product	Tap