

Machine tap, uncoated, UNC: 1/4-20



Order data

Order number	137862 1/4-20
GTIN	4045197594914
Item class	12H

Description

Version:

Sturdy design, with right-hand chip flutes. HSS-E

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC
Tool material: HSS E
Standard: DIN 371
Threads per inch: 20
Thread Ø: 6.35 mm
Overall length L: 80 mm
Shank Ø D₅: 7 mm

Shank square \square : 5.5 mm Tapping hole \varnothing : 5.1 mm

Technical description

Number of clamping slots	3
Thread Ø	6.35 mm
Threads per inch	20
Thread pitch	1.27 mm
Number of cutting edges Z	3
Tapping hole Ø	5.1 mm
Standard	DIN 371
Tool material	HSS E

Shank Ø D _s	7 mm
Overall length L	80 mm
Shank square □	5.5 mm
Thread depth	10.98 mm
Thread type	UNC
Thread size	1/4-20 UNC
Coating	uncoated
Flank angle	60 degrees
Tolerance class	2B
Taper lead form	С
Helix angle	15 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Тар