



Machine tap, uncoated, UNC: 4-40



Order data

Order number	137862 4-40
GTIN	4045197594860
Item class	12H

Description

Version:

Sturdy design, with right-hand chip flutes. HSS-E

Application:

For UNC uniform coarse threads ASME – B1.1.

Thread type: UNC

Tool material: HSS E

Standard: DIN 371

Threads per inch: 40

Thread Ø: 2.84 mm

Overall length L: 56 mm

Shank Ø D_s: 3.5 mm

Shank square □: 2.7 mm

Tapping hole Ø: 2.35 mm

Technical description

Threads per inch	40
Number of clamping slots	3
Thread pitch	0.635 mm
Tapping hole Ø	2.35 mm
Thread Ø	2.84 mm
Number of cutting edges Z	3
Standard	DIN 371
Tool material	HSS E

Shank $\varnothing D_s$	3.5 mm
Overall length L	56 mm
Shank square \square	2.7 mm
Thread depth	5.7 mm
Thread type	UNC
Thread size	4-40 UNC
Coating	uncoated
Flank angle	60 degrees
Tolerance class	2B
Taper lead form	C
Helix angle	15 degrees
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap