

Machine tap, uncoated, Rc: 1-11



Order data

Order number	138120 1-11
GTIN	4045197585738
Item class	11H

Description

Version:

The short shank overhangs less and hence is more stable.

Application:

For use as machine tap or for cleaning existing threads by hand. **Tapered** Whitworth pipe thread (**BSPT**) to **ISO 7/1** and **BS21**, for joints with sealant in the thread. See the table for the specified minimum size of the tapping hole.

Recommendation:

Tapping hole Ø A:

Pre-drill a plain hole **without using a reamer. Variant A** can be used if there is no risk of sealing problems.

Tapping hole Ø B:

Pre-drill a plain hole and then **ream it using a 1:16 taper reamer (see No. 162650).** The taper bore \varnothing can then be checked laterally by reference to the D_{max} check dimension (see table).

Variant B for drilling the tapping hole offers the best process reliability for the tapping operation and at the same time ensures the most reliable seal in the thread.

Threads per inch: 11 Overall length L: 110 mm Shank Ø D_s: 25 mm Shank square □: 20 mm Tapping hole Ø A: 29.2 mm Tapping hole Ø B: 29.1 mm

Technical description

Number of clamping slots	6
--------------------------	---

Tapping hole ∅ B	29.1 mm
Number of cutting edges Z	6
Thread gauge Ø D _{max} JS11	30.29 mm
Thread Ø	33.24 mm
Tapping hole Ø A	29.2 mm
Thread pitch	2.309 mm
Threads per inch	11
Tapping hole minimum depth	28.3 mm
Shank Ø D _s	25 mm
Overall length L	110 mm
Shank square □	20 mm
Thread depth	75 mm
Thread size	Rc1-11
Coating	uncoated
Thread type	Rc
Flank angle	55 degrees
Tool material	HSS E
Standard	DIN 2181
Thread standard	DIN EN 10226-2
Taper lead form	С
Taper ratio	1:16
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Тар

