

Garant
Fluteless machine tap without oil grooves HSS-E-PM 6HX, TiN, M: M3,5

Order data

Order number	139115 M3,5
GTIN	4045197508539
Item class	11H

Description
Version:

DIN 2174 (\approx **DIN 371** \leq M10; \approx **DIN 376** \geq M12).

The **innovative polygon form** permits a wide application spectrum. The **multi-function layer structure** achieves **maximum service life** even in **high-tensile materials**.

Tolerance class: ISO 2X 6HX

Thread pitch: 0.6 mm

Overall length L: 56 mm

Shank $\varnothing D_s$: 4 mm

Shank square \square : 3 mm

Tapping hole \varnothing with guide value: 3.25 mm

Technical description

Thread \varnothing	3.5 mm
Thread pitch	0.6 mm
Number of cutting edges Z	3
Number of clamping slots	3
Shank $\varnothing D_s$	4 mm
Shank square \square	3 mm
Overall length L	56 mm
Tapping hole \varnothing with guide value	3.25 mm
Tolerance class	ISO 2X 6HX
Thread depth	5.25 mm

Thread size	M3.5
Coating	TiN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5xD for blind holes and through holes
Cutting direction	right-hand
Colour ring	blue
Type of product	Fluteless tap