

Garant
Fluteless machine tap without oil grooves HSS-E-PM 6GX, TiN, M: M4

Order data

Order number	139135 M4
GTIN	4045197508782
Item class	11H

Description
Version:
DIN 2174 (\approx **DIN 371** \leq M10; \approx **DIN 376** \geq M12).

The **innovative polygon form** permits a wide application spectrum. The **multi-function layer structure** achieves **maximum service life** even in **high-tensile materials**.

Tolerance class: ISO 3X / 6GX = **Oversize 0.02 – 0.04 mm**.

Application:

For components which are **galvanised after threading** or which shrink slightly when hardened.

Tolerance class: ISO 3X 6GX

Thread pitch: 0.7 mm

Overall length L: 63 mm

Shank $\varnothing D_s$: 4.5 mm

Shank square \square : 3.4 mm

Tapping hole \varnothing with guide value: 3.7 mm

Technical description

Number of cutting edges Z	4
Thread \varnothing	4 mm
Number of clamping slots	4
Thread pitch	0.7 mm
Shank $\varnothing D_s$	4.5 mm
Shank square \square	3.4 mm
Overall length L	63 mm
Tapping hole \varnothing with guide value	3.7 mm

Tolerance class	ISO 3X 6GX
Thread depth	6 mm
Thread size	M4
Coating	TiN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E PM
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5xD for blind holes and through holes
Cutting direction	right-hand
Colour ring	green
Type of product	Fluteless tap