



## Fluteless machine tap without oil grooves HSS-E 6GX, TiAlN, M: M3



### Order data

Order number	139142 M3
GTIN	4045197446633
Item class	12H

### Description

#### Version:

**DIN 2174** ( $\approx$  **DIN 371**  $\leq$  M10;  $\approx$  **DIN 376**  $\geq$  M12).

**Tolerance class:** ISO 3X / 6GX = **Oversize 0.02 – 0.04 mm.**

#### Application:

For components which are **galvanised after threading** or which shrink slightly when hardened.

Tolerance class: ISO 3X 6GX

Thread pitch: 0.5 mm

Overall length L: 56 mm

Shank  $\varnothing D_s$ : 3.5 mm

Shank square  $\square$ : 2.7 mm

Tapping hole  $\varnothing$  with guide value: 2.8 mm

### Technical description

Thread pitch	0.5 mm
Thread $\varnothing$	3 mm
Number of clamping slots	3
Number of cutting edges Z	3
Shank $\varnothing D_s$	3.5 mm
Shank square $\square$	2.7 mm
Overall length L	56 mm
Tapping hole $\varnothing$ with guide value	2.8 mm
Tolerance class	ISO 3X 6GX

Thread depth	4.5 mm
Thread size	M3
Coating	TiAlN
Thread type	M
Flank angle	60 degrees
Tool material	HSS E
Standard	DIN 2174
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	right-hand
Colour ring	green
Type of product	Fluteless tap